Xerox® AltaLink® Color Multifunction Printers

C8230/C8235/C8245/C8255/C8270

Xerox® AltaLink® C8200 Series Color Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to **www.ConnectKey.com**.

System Specification	AltaLink® C8230	AltaLink® C8235	AltaLink® C8245	AltaLink® C8255	AltaLink® C8270
Speed[1] Color/Black-and-White	Up to 30/30 ppm	Up to 35/35 ppm	Up to 45/45 ppm	Up to 55/55 ppm	Up to 70/70 ppm
Monthly Duty Cycle[2]	Up to 90,000 pages	Up to 110,000 pages	Up to 200,000 pages	Up to 300,000 pages	Up to 300,000 pages
Hard Drive/Processor/ Memory	Minimum 256 GB NVMe SSD/**Optional:** 1TB NVMe SSD/Intel Atom® Quad Core 1.91 GHz/4 GB system memory (8 GB system memory AltaLink® C8270)				
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 2.0 direct print, NFC, **Optional:** Wi-Fi®/Wi-Fi Direct® with Xerox® Dual Band WiFi® and Bluetooth® Kit (Bluetooth for iBeacon(™))				
Controller Features	Configuration Cloning, Configuration Watchdog, Fleet Orchestrator, Remote Control Panel, Unified Address Book, Security Dashboard, Adaptive Learning				
Optional Controller	Xerox® EX-c AltaLink® Print Server Powered by Fiery®				
Copy and Print					
Copy and Print Resolution	**Copy:** Up to 600 x 600 dpi; **Print:** Up to 1200 x 2400 dpi				
First-Print-Out Time (as fast as)	5.7/4.2 seconds black-and-white		4.9 seconds color/3.6 seconds black-and-white	4.5 seconds color/3.2 seconds black-and-white	3.7 seconds color/2.8 seconds black-and-white
First-Copy-Out Time (as fast as) (from platen/ warmed-up state)	6.0 seconds color/4.2 seconds black-and-white		5.5 seconds color/3.9 seconds black-and-white	4.6 seconds color/3.6 seconds black-and-white	4.0 seconds color/2.8 seconds black-and-white
Page Description Language	Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c/PCL® 6, Adobe Embedded Print Engine (AEPE)				
Print Features	Application Defaults, Bi-directional Real-time Status, Booklet Layout, Encrypted Secure Print, Hold All Jobs, Imaging Security with AltaLink's proprietary marking and infrared detection technology, Job Identification, Job Monitoring, Long Sheet (Banner) Printing, Print Around, Print from Cloud Repositories (Dropbox, OneDrive, and Google Drive), Print from USB, Print on Alternate Paper, Scaling, Store and Recall Driver Settings, Two-sided Printing (as default), Xerox® Earth Smart Driver Settings, Microsoft Universal Print/IPP with Print Support Application; **Optional:** Print from and Scan to Xerox® DocuShare® Go content management				
Mobile and Cloud-ready					
Universal Print Ready	Microsoft Universal Print is a cloud print service, available to Microsoft 365 subscribers. It removes the need for on-site print servers and leverages the built-in drivers included in the Windows 10 and 11 PCs. You can enjoy the benefits of cloud hosting with a driverless setup for all Windows 10 and 11 clients. Utilize the Print Support App (PSA) by Xerox (Requires installation of Xerox Print and Scan Experience App) to gain access to the Xerox Print Properties user interface.				
Mobile Connectivity	Near Field Communication (NFC); **Optional:** Wi-Fi Direct®, Wi-Fi® (802.11 b/g/n/ac), AirPrint™ (iOS) including iBeacon™ (Bluetooth®)				
Mobile Printing	Mopria® Print, Apple™ AirPrint™, Xerox® Print Service (Android), @PrintByXerox App, **Xerox Easy Assist App**, Xerox® Workplace Mobile App (iOS/Android); **Optional:** AirPrint™ (iOS) including iBeacon™ (Bluetooth® for AirPrint Discovery)				
Mobile Scanning	Mopria® Scan, Apple™ AirPrint™, **Xerox Easy Assist App**; **Optional:** Xerox® Workplace Mobile App (iOS/Android)				
Mobile Apps and Xerox App Gallery	Automate everyday processes with optional apps that translate, redact, eSign, personalize, print, convert, route, collaborate, and communicate. Visit **xerox.com/WorkplaceApps** to find apps by industry or workflow.				
Xerox® Workflow Central Platform	**Optional:** One-platform consistency for seamless productivity across computers, mobile devices and printers. With Workflow Central's ever-expanding suite of cloud-based workflows, you can change documents into audio files for easy listening, convert PDF or image files to popular Microsoft formats for shareability with a wider audience, turn handwriting into legible, editable and shareable text, translate to/from over 40 different languages, and automatically redact Personal Identifiable Information using set words or phrases **xerox.com/en-us/office/software-solutions/workflow-central**				

COPIERWORKS

Xerox® AltaLink® C8230/C8235/C8245/C8255/C8270 Color Multifunction Printer

Xerox® Workplace Suite and Xerox® Workplace Cloud	**Optional:** Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution **xerox.com/en-us/office/print-management-solutions**
Cloud Identity Provider (IdP) Integration	Use your desktop, laptop, or mobile login credentials to log in to your AltaLink® MFPs with direct connections to popular cloud identity providers Okta, Ping Identity, and Microsoft® Azure
Scan	
Standard Features	**Destinations:** Scan to USB/PC via USB port/Email/Network (SMB, sFTP, FTP, HTTP, HTTPS destinations); **File Formats:** PDF, PDF/A, JPEG, TIFF; **Convenience Features:** 1-Touch Apps, Imaging Security with AltaLink's proprietary marking and infrared detection technology, Optical Character Recognition (OCR), Password-protected PDF, Scan Preview, Scan to Folder, Scan to Home, Scan to Print, Searchable PDF, Single/Multi-Page PDF/TIFF, Touchless Workflow Accelerators, TWAIN Support, Unified Address Book
Optional Features	Native Scan to Cloud Repositories (Dropbox, OneDrive, and Google Drive). Xerox® Scanning App for DocuShare®, other solutions available through various Xerox® Business Innovation Partners at **xerox.com/Software-Solutions,** Print from and Scan to Xerox® DocuShare® Go content management
Fax	
Standard Features	Fax Build Job, Network Server Fax Enablement
Optional Features	Walk-up Fax one line, two-line available in select geographies, includes LAN Fax, Direct Fax, Fax Forward to Email, or SMB Share, Support for Fax over Voice over IP
Security	
Standard Features	802.1x, Access Control, Audit Log, Automated threat response through Trellix DXL/Cisco® pxGrid integration, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) Integration, Configuration Watchdog, Security Dashboard, Encrypted Secure Print, Encrypted Storage Drive (AES 256-bit), FIPS 140-3 (interim certification), Firmware Verification, HTTPS, Imaging Security (copy, print, scan, email) with AltaLink's proprietary marking and infrared detection technology, IPsec, Job Level Encryption via HTTPS and Drivers, Local Authentication (Internal Database), Microsoft Universal Print/IPP with Print Support Application (Secure Print and Secure Release), Network Authentication, Port/IP/Domain Filtering, Security Certificates utilizing ECDSA, Security Dashboard, Security Templates, Serverless Card Authentication, sFTP and Encrypted Email, SHA-256 Hash Message Authentication, SIEM integration (e.g Splunk, LogRhythm, Trellix ESM, and Microsoft Sentinel), Signed Email, SNMPv3, TLS1.1/1.2/1.3, Trusted Platform Module (2.0), Trellix Embedded Control Allowlisting, Trellix ePolicy Orchestrator®, Trusted Boot, User Access and Internal Firewall, User Permissions, Common Criteria Certification under collaborative Protection Profile for Hardcopy Devices (HCD cPP v1.0E) pending, EU Radio Equipment Directive (RED) Articles 3(3)(d) and (e) compliant, NFC Tap Authentication with Xerox® Easy Assist App
Optional Features	Trellix Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET)[3], Xerox® Integrated RFID Card Reader, Encrypted Storage Drive (AES 256-bit, FIPS 140-3), Xerox® Workplace Cloud/Suite Print Management and Content Security; WPA2™ and WPA3™ with Xerox® Dual Band WiFi® and Bluetooth® Kit (Bluetooth for iBeacon(™)); Xerox Workplace Cloud/Suite Print Management and Content Security, learn more at **xerox.com/WorkplaceSolutions**
Print Management	
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement
Optional Features	Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox® Business Innovation Partners. Xerox® Virtual Print Management Service; learn more at **xerox.com/PrintManagement**
Embedded Pre-installed Artificial Intelligence Apps	
Limited Use Standard Features	**Xerox® Note Converter App** utilizes the power of AI to make sense of handwriting, allowing you to quickly convert your notes into an MS Word document or a digital file. Easily edit, store, and share your notes with everyone in that important meeting you just left, saving you precious time. **Learn more.** **Xerox® Summarizer App** creates a summary of documents for viewing, printing, and emailing. Using artificial intelligence (AI), Xerox® Summarizer condenses dozens or even hundreds of pages by reducing the original scanned document to a percentage of the original or by creating a short and concise interpretation of the source text. **Learn more.** **Xerox® Auto-Redaction App** takes advantage of cutting-edge AI technology in Google's Data Loss Prevention (DLP) software, which allows you to select preset Personally Identifiable Information (PII) or custom words and phrases and then automatically redact it. **Learn more.** See Xerox® AltaLink® 8200 Multifunction Printer Series Embedded AI Apps **Frequently Asked Questions (FAQs)** for more information

COPIERWORKS

Xerox® AltaLink® C8230/C8235/C8245/C8255/C8270 Color Multifunction Printer

Features and Accessories

Single-pass Duplex Automatic Document Feeder (DADF) saves time by simultaneously scanning both sides of a document with up to 270 impressions per minute (ipm).

USER INTERFACE

Intuitive Tablet-like 10.1-inch Color Touchscreen is customizable and lets you perform tasks in just a few taps. Try it out at www.xerox.com/SIM7.

INNOVATIVE TECHNOLOGIES

Xerox® Integrated RFID Card Reader (optional) adds card-based authentication with support for over 90 access cards.

Near Field Communication (NFC) Tap-to-Pair allows users to tap their mobile devices to the AltaLink® C8200 Series user panel and quickly connect with the MFP.

Smart Proximity Sensor detects when users are nearby. It conserves energy during inactive periods and automatically activates the device when a user approaches.

PAPER INPUT[4]

Two 520-sheet Adjustable Trays (common with all configurations). Tray 1 handles media sizes up to 11.7 x 17 in./A3 and Tray 2 handles media sizes up to 12 x 18 in./SRA3.

Envelope Kit (optional — replaces Tray 1) provides feeding of up to 60 envelopes.



High Capacity Tandem Tray Configuration holds a total paper capacity of up to 3,140 sheets.

Four Tray Module Configuration (available for C8230/C8235) holds a total of up to 2,180 sheets.

Bypass Tray handles up to 100 sheets; Custom sizes: 3.5 x 3.9 in. to 12.6 x 52 in./89 x 98 mm to 320 x 1,320 mm.

High Capacity Feeder (optional) holds 3,000 sheets of letter/A4 paper, increasing the maximum paper capacity to 6,140 sheets.

LONG SHEET PRINTING

Long Sheet Feed Kit (optional) provides the ability to print up to 12.6 x 52 in./ 320 x 1,320 mm media.

PAPER OUTPUT/FINISHERS[4]

Office Finisher (optional) provides advanced finishing functions, optional crease/score and saddle-stitch booklet, capable of 60-page booklets (2 to 15 sheets).

Business Ready (BR) Finisher (optional) gives you advanced finishing functions at a great value.

C-Fold/Z-Fold Unit (optional) adds C-fold, Z-fold and Z-half-fold capability to the BR Finisher or BR Booklet Maker Finisher.

BR Booklet Maker Finisher (optional) creates 64-page saddle-stitched booklets (2 to 16 sheets).

Dual Offset Catch Tray (available when no finishers are installed; Single Offset Catch Tray with finishers).

Integrated Office Finisher (optional with C8230/C8235/ C8245/C8255) provides 500-sheet stacking and 50-sheet, 2-position stapling.

Convenience Stapler (optional) staples up to 50-sheets of 20 lb./75 gsm media.

copierworks.com

Xerox® AltaLink® C8230/C8235/C8245/C8255/C8270 Color Multifunction Printer

Device Specification					
Control Panel Languages	US English, Catalan, Czech, Danish, German, International English, International Spanish, International French, Croatian, Italian, Hungarian, Dutch, Norwegian, Polish, Brazilian Portuguese, Romanian, Finnish, Swedish, Turkish, Greek, Russian, Ukrainian, Arabic				
Accessories					
Optional	1TB NVMe SSD Digital Storage Booklet Maker for Office Finisher BR (Business Ready) Finisher (requires Horizontal Transport Kit) BR Booklet Maker Finisher (requires Horizontal Transport Kit) C-fold/Z-fold Unit for BR Finisher or BR Booklet Maker Finisher Convenience Stapler (includes Work Surface5) Envelope Tray (Replaces Tray 1) Foreign Device Interface (Also known as Auxiliary Access Device Interface) for third-party access control devices, such as coin machines and card readers High Capacity Feeder 3000 A4/Letter Hole Punch (2/3, 2/4, Swedish) Horizontal Transport Kit Integrated Office Finisher (Available with AltaLink® C8230/C8235/C8245/C8255) Long Sheet Feed Kit (banner printing) Trellix Integrity Control Enablement Kit Multi-feed Detection Kit (AltaLink® C8270 only) Office Finisher Scan To Cloud Enablement Kit Smart Card Enablement Kit[3] Unicode Font Kit USB Keyboard/Shelf Kit Walk-up Fax (One- or Two-line options, includes LAN Fax) Wi-Fi®/Wi-Fi Direct® with Xerox® Dual Band WiFi® and Bluetooth® Kit (Bluetooth for iBeacon™) Xerox® EX-c AltaLink® Print Server Powered by Fiery® Xerox® Integrated RFID Card Reader Kit				
Electrical Requirements	**AltaLink® C8230**	**AltaLink® C8235**	**AltaLink® C8245**	**AltaLink® C8255**	**AltaLink® C8270**
North America	Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 15 A				Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 20 A
Europe	Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 10 A				Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 10 A

COPIERWORKS.com

Device Specification (continued)					
Power Consumption	**AltaLink® C8230**	**AltaLink® C8235**	**AltaLink® C8245**	**AltaLink® C8255**	**AltaLink® C8270**
Running (Average)	115V: 576 watts 230V: 586 watts	115V: 600.3 watts 230V: 595.8 watts	115V: 717 watts 230V: 674 watts	115V: 806 watts 230V: 760 watts	115V: 929 watts 230V: 908 watts
Standby Mode	115V: 67 watts 230V: 71 watts	115V: 64 watts 230V: 70 watts	115V: 71 watts 230V: 71 watts	115V: 72 watts 230V: 70.3 watts	115V: 91.1 watts 230V: 79 watts
Auto Off/Sleep Mode	115V: 0.57 watts 230V: 0.59 watts (Default time to sleep mode = 0 minutes)	115V: 0.57 watts 230V: 0.59 watts (Default time to sleep mode = 0 minutes)	115V: 0.58 watts 230V: 0.60 watts (Default time to sleep mode = 0 minutes)	115V: 0.58 watts 230V: 0.60 watts (Default time to sleep mode = 0 minutes)	115V: 0.56 watts 230V: 0.59 watts (Default time to sleep mode = 0 minutes)
Warm-up (from Off)	As fast as 82 seconds				
Recovery from Sleep	As fast as 4.5 seconds				
Operating Environment					
Required Temperature Range	50 to 82° F/10 to 28° C				
Required Relative Humidity	15% to 85%				
Sound Power Levels	Operating: 63.7/64.2 dB(A) Standby: 40.0/40.0 dB(A)		Operating: 65.2/67.3 dB(A) Standby: 43.0/43.0 dB(A)		Operating: 70.4 dB(A) Standby: 43.0 dB(A)
Dimensions and Weight					
Base Configuration	Width: 24.4 in./620 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 316 lb./143.1 kg				Width: 24.4 in./620 mm Depth: 31.2 in./793 mm Height: 46 in./1,169 mm Weight: 352.1 lb./159.7 kg
With Integrated Office Finisher (C8230/C8235/ C8245/C8255)	Width: 32.2 in./819 mm Depth: 28.5 in./723 mm Height: 44.55 in./1,130 mm Weight: 340 lb./154.2 kg				N/A
With Office Finisher (with Booklet Maker)	Width: 47.5 in./1,207 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 402.3 lb./182.5 kg				Width: 47.5 in./1207 mm Depth: 31.2 in./793 mm Height: 46 in./1,169 mm Weight: 439 lb./199 kg
Base Configuration with Business Ready (BR) Finisher	Width: 55 in./1,395 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 412.3 lb/187 kg				Width: 55 in./1,395 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 448.4 lb./203.4 kg
Base Configuration with BR Booklet Maker Finisher	Width: 59 in./1,496.3 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 449.7 lb./204 kg				Width: 59 in./1,496.3 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 486.3 lb./220.6 kg
Base Configuration with BR Booklet Maker Finisher and C-fold/Z-fold Unit	Width: 64.3 in./1,632 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 560.6 lb./254.3 kg				Width: 64.3 in./1,632 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 597.2 lb./270.9 kg
Base Configuration with BR Booklet Maker Finisher, C-fold/Z-fold Unit and High Capacity Feeder	Width: 93 in./2,361 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 628.8 lb./285.2 kg				Width: 93 in./2,361 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 665.8 lb./302 kg
System Certifications/Regulatory Compliance					
Certifications	To view the latest list of certifications, go to **xerox.com/OfficeCertifications**				

COPIERWORKS.COM

Xerox® AltaLink® C8230/C8235/C8245/C8255/C8270 Color Multifunction Printer

Paper Handling	AltaLink® C8230	AltaLink® C8235	AltaLink® C8245	AltaLink® C8255	AltaLink® C8270
Single-pass Duplex Automatic Document Feeder (DADF)					
Capacity[4]	130 sheets				250 sheets
Speed (Up to)	82 ppm black-and-white and color (simplex) 161 ipm black-and-white and color (duplex)				135 ppm black-and-white and color (simplex) 270 ipm black-and-white and color (duplex)
Paper Sizes Sensed	3.4 x 4.9 in. to 11.7 x 17 in./85 x 125 mm to 297 x 432 mm				
Weights	16 to 32 lb. bond/60 to 128 gsm				
Bypass Tray (Standard)					
Capacity[4]	100 sheets				
Sizes	**Custom Sizes:** 3.5 x 3.9 in. to 12.6 x 52 in./89 x 98 mm to 320 x 1320 mm (SEF); **Optional:** Long Sheet Feed Kit (Banner Printing)				
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm, **Long sheets/banners** (>19 in./483 mm): 28lb Bond - 120lb Index/106 - 220 gsm				
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole Punched Letterhead Lightweight Lightweight Card Stock Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain-Reloaded Preprinted Recycled Transparencies **Long Sheets/Banners:** Card Stock Card Stock Reloaded Lightweight Card Stock Lightweight Card Stock Reloaded				
Trays 1 and 2 (Standard)					
Capacity[4]	520 sheets each				
Sizes	**Tray 1:** Custom Sizes: 5.5 x 7.2 in. to 11.7 x 17 in./140 x 182 mm to 297 x 432 mm (SEF) **Tray 2:** Custom Sizes: 5.5 x 7.2 in. to 12 x 18 in./140 x 182 mm to SRA3 (SEF)				
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm				
Media Types	Bond Card Stock Card Stock Reloaded Custom Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain-Reloaded Preprinted Recycled Transparencies				

COPIERWORKS.COM

Xerox® AltaLink® C8230/C8235/C8245/C8255/C8270 Color Multifunction Printer

Paper Handling (continued)	AltaLink® C8230	AltaLink® C8235	AltaLink® C8245	AltaLink® C8255	AltaLink® C8270
Four Tray Module (Trays 3 and 4) (Available on C8230/C8235)					
Capacity[4]	**Tray 3:** 520 sheets **Tray 4:** 520 sheets				
Sizes	**Trays 3 and 4:** 5.5 x 7.2 in. to 12 x 18 in./140 x 182 mm to SRA3 mm (SEF)				
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm				
Media Types	Bond Card Stock Card Stock Reloaded Custom Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain-Reloaded Preprinted Recycled Transparencies				
High Capacity Tandem Tray (Available with all models)					
Capacity[4]	**Tray 3:** 867 sheets **Tray 4:** 1,133 sheets				
Sizes	8.5 x 11 in./A4, JIS B5, Executive (7.25 x 10.5 in) LEF				
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm				
Media Types	Bond Card Stock Custom Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted				
Envelope Tray (Optional - Replaces Tray 1)					
Capacity[4]	Up to 60 envelopes				
Sizes	#10 Commercial (9.25 x 4.125 in.)/Monarch, DL, C5 Custom Sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in./98 x 148 mm to 162 x 241 mm				
Weights	20 lb. to 24 lb. bond/75 to 90 gsm				
High Capacity Feeder (HCF) (Optional with all models)					
Capacity[4]	3,000 sheets				
Sizes	Standard Sizes: 8.5 x 11 in. or 7.25 x 10.5 in./A4 or B5 LEF				
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm				
Total Capacity					
Device Total Capacity[4]	Four Tray Module: 2,180 sheets Four Tray Module with High Capacity Feeder: 5,180 sheets High Capacity Tandem Tray Module: 3,140 sheets High Capacity Tandem Tray Module with High Capacity Feeder: 6,140 sheets				

COPIERWORKS
Your local dealer in BC · Buy, lease or rent · copierworks.com · (604) 838-7368

Xerox® AltaLink® C8230/C8235/C8245/C8255/C8270 Color Multifunction Printer

Finishing	AltaLink® C8230	AltaLink® C8235	AltaLink® C8245	AltaLink® C8255	AltaLink® C8270
Output Trays (Standard) (Dual Offset Catch Trays not available with Integrated Office Finisher and limited to one with Office Finisher and BR Finishers)					
Stacking Tray Capacity[4]	Dual Offset Catch Tray: Up to 250 sheets each Left Side Face up Tray: Up to100 sheets				
Integrated Office Finisher (Optional with AltaLink® C8230/C8235/C8245/C8255 only)					
Stacking Tray Capacity[4]	500 sheets of 20 lb. bond/80 gsm – 8.5 x 11 in./A4 or 250 sheets of 20 lb. bond/80 gsm – 11 x 17 in./A3				
Sizes	3.5 x 3.9 in. to 11.7 x 17 in./89 x 98 mm to 297 x 432 mm				
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm				
Stapling	Single/Dual Position Auto-Stapling: 50 sheets maximum: Letter/A4/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers)				
Office Finisher (Optional)					
Stacking Tray Capacity[4]	2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4)				
Stacking Tray Sizes	8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432 mm				
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm				
Multiposition Stapling	50 sheets maximum: Letter/A4/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers)				
Hole Punch (Optional)	**North America:** 2/3-hole punch **Europe:** 2/4-hole punch **Optional:** 4-hole "Swedish" punch				
Booklet Maker for Office Finisher (Score/Crease, Saddle-stitch Staple) (Optional)					
Top Tray Capacity[4]	40 booklets (2-15 sheets per booklet – 20 lb./80 gsm or less)				
Sizes	Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Tabloid – 11 x 17 in./A3 SEF				
Saddle-Stitch Stapling	2-15 sheets/8-60 page booklet 16 lb. bond to 80 lb. cover/64 to 220 gsm				
Score/Crease	1-15 sheets/unstapled 16 lb. bond to 28 lb. bond/64 to 105 gsm				
Business Ready (BR) Finisher (Optional) (Requires Horizontal Transport Kit)					
Capacity[4]	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8.5 x 14 in./A3 or 200 sets (single-position staple) 8.5 x 11 in./A4				
Sizes	3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray 7.25 x 10.5 in. to 12.6 x 19 in./182 x 203 mm to 320 x 488 mm for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling				
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm				
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4, and B5 sizes supported				
Hole Punch	**North America:** 2/3-hole punch **Europe:** 2/4-hole punch **Optional:** 4-hole "Swedish" punch				
BR Booklet Maker Finisher (Optional) (Requires Horizontal Transport Kit)					
Capacity[4]	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3 unstapled or 200 stapled sets of 8.5 x 11 in./A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in./A3				
Sizes	3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray 7.25 x 10.5 in. to 12.6 x 19 in./182 x 203 mm to 320 x 488 mm for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling				
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm				
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4, and B5 sizes supported				
Hole Punch	**North America:** 2/3-hole punch **Europe:** 2/4-hole punch **Optional:** 4-hole "Swedish" punch				
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported				

COPIERWORKS.com

Finishing (continued)	AltaLink® C8230	AltaLink® C8235	AltaLink® C8245	AltaLink® C8255	AltaLink® C8270
C-fold/Z-fold Unit (Optional with BR Finisher and BR Booklet Maker Finisher)					
Types	C-fold, Z-fold, and Z-half-fold				
Capacity[4]	40 sheets				
Sizes	C-fold and Z-fold: Letter – 8.5 x 11 in./A4 SEF only Z-half-fold: Tabloid – 11 x 17 in./A3 only				
Weights	16 lb. to 24 lb. bond/64 to 90 gsm				
Output Trays	Envelope Tray: C-fold, Z-fold, and Tri-fold Stacker Tray or Top Tray: Z-half-fold				
Convenience Stapler (Optional - Includes Work Surface[5]**)**					
Capacity[4]	50-sheet stapling 5,000 staples Requires separate power outlet				
Copy	**AltaLink® C8230**	**AltaLink® C8235**	**AltaLink® C8245**	**AltaLink® C8255**	**AltaLink® C8270**
First-Copy-Out Time (from platen/warmed up Color/Black-and-White)	As fast as 6.0 seconds/ As fast as 4.2 seconds		As fast as 5.6 seconds/ As fast as 3.9 seconds	As fast as 4.6 seconds/ As fast as 3.6 seconds	As fast as 4.1 seconds/ As fast as 2.8 seconds
Sides (input-output)	1-1, 1-2, 2-2, 2-1				
Quantity	1 to 9,999				
Resolution (max)	Up to 600 x 600 dpi				
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments				
Concurrency	Program-ahead to allow job to be queued while initial job is processed (Copy, Print, Fax, and Scan)				
Copy Features	Annotation and Bates™ stamping (with color capability and font size adjustment) Authentication for Services (i.e., Color Copy) Auto Paper Select Auto Reduction & Enlargement (to fit selected paper size) Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job (enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Imaging Security Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Single Color Stapling Touchless Workflow Accelerators Transparencies				

COPIERWORKS.com

Xerox® AltaLink® C8230/C8235/C8245/C8255/C8270 Color Multifunction Printer

Print	AltaLink® C8230	AltaLink® C8235	AltaLink® C8245	AltaLink® C8255	AltaLink® C8270
First-Print-Out Time (as fast as)	5.7/4.2 seconds black-and-white		4.9 seconds color/3.6 seconds black-and-white	4.5 seconds color/3.2 seconds black-and-white	3.7 seconds color/2.8 seconds black-and-white
Resolution (up to)	1200 x 2400 dpi				
Print Features	Application Defaults Banner Sheet Enable/Disable Booklet Layout Cover Selection Custom Color Options (Color By Words) Bi-directional Real-time Status Delay Print (specific time) User Permissions Finishing Fit to New Paper Size Hold All Jobs Image Options (Toner Saver, Resolution (Standard, Enhanced, High)) Imaging Security Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Layout/Watermark Long Sheet/Banner N-up (up to 16 pages per sheet) Paper Selection by Attribute Sample Set Print From Cloud Repositories (Dropbox, OneDrive, and Google Drive) Saved Job (color jobs can be printed as monochrome) Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) Two-sided Printing (as default)				
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, PCL Color jobs can be printed as black-and-white				
Operating Systems	Windows 10 (32 and 64 bit) Windows 11 (64 bit) MacOS 12.x, 13.x, 14.x Red Hat Enterprise Linux 7.x, 8.x, 9.x Ubuntu 18.04, 20.04, 22.04, 23.04, 24.0 OpenSUSE Linux Server 15.5 MS Windows 2012 Server (64 bit) MS Windows 2016 Server (64 bit) MS Windows 2019 Server (64 bit) MS Windows 2022 Server (64 bit) Red Hat Linux Server 7.x, 8.x SuSe Linux Server 12.2-12.4, 15.x **Note:** For latest supported versions please visit our Drivers & Downloads page and specify your device at **support.xerox.com**				
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD Microsoft Windows Networking over IP Bonjour®/AirPrint™ IPv6 Most protocols not in use can be disabled				
Font Capability	PCL: 93 scalable fonts, line printer, and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts				
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade, and manage Xerox® Devices and non-Xerox devices from a single driver It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management Support for Microsoft Universal Print with Print Support Application (PSA)				
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy, and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos®, and others				
Unified Address Book for Fax, Email, and Scan to...					
Features	Services supported: Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favorites for quick access of all services supported				

Copierworks.com

Xerox® AltaLink® C8230/C8235/C8245/C8255/C8270 Color Multifunction Printer

Scan	AltaLink® C8230	AltaLink® C8235	AltaLink® C8245	AltaLink® C8255	AltaLink® C8270
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)				
Input Speed (up to)	82 ppm black-and-white and color (simplex) 161 ipm black-and-white and color (duplex)				135 ppm black-and-white and color (simplex) 270 ipm black-and-white and color (duplex)
Resolution	150 x 150 dpi to 600 x 600 dpi				
Bit Depth	1-bit (black-and-white), 8-bit (grayscale), 24-bit (color)				
Maximum Scan Area	11 x 17 in./A3				
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other multifunction printers' confirmation sheet options				
Network Protocols	sFTP, FTP, SMB, HTTP, HTTPS				
File Compression	Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression – single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for black-and-white and within MRC)) Linearized PDF/PDF/A				
Document Management Fields (Metadata)	Features only available in Network Scan to File Templates: • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value, and other configurations • Customized fields viewed on user interface for variable data input Scan To with Metadata • Embedded in scan files using XMP formats • Works with expert systems workflow				
Scan Features	Auto Background and Shadow Suppression Bound Originals Create scan files based on image count Compression Quality/File Size Control Edge Erase Imaging Security Mixed Size Originals Scan Build Job Original Type (Photo and Text, Photo, Text, Map, Newspaper/Magazine) Reduction/Enlargement Scan to Home Scan to Mailbox Scan to Network (using FTP/sFTP/SMB/HTTP/HTTPS) Scan to Network Folder (usiing FTP/sFTP/SMB/HTTP/HTTPS) Single Touch Scan buttons (up to 10) Size for Size (for mixed size originals) TWAIN Support/WIA 2.0 Support				
Scan to Email (Standard)					
Scan Features	• Auto send to self • Create scan files based on image count • Email signatures (6 lines each of 128 character max), email message body (user configurable), email Embedded Web Server confirmation sheet options • Email signing (requires Smart Card option) • Scan to Email S/MIME Encryption • Touchless Workflow Accelerators				
Directory Access	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino), Device Address Book				
Scan To					
Standard Features	Create scan files based on image count Scan Preview Scan to Email Scan to Network (using sFTP) Scan to Network Folder (using sFTP) Scan to PC via USB port Scan to PC/Server Client (SMB or FTP) Scan to Print Scan to USB Touchless Workflow Accelerators				
Optional Features	Native Scan to Cloud Repositories (Dropbox, OneDrive, and Google Drive)[3]				
Xerox ConnectKey Scan Apps					
Scanning Apps and Xerox App Gallery	Scan to: Dropbox, Google Drive, Microsoft OneDrive, Microsoft Office 365, Box, Xerox® Workplace Mobile App (iOS/Android) See the full list of apps available in the Xerox App Gallery: **xerox.com/AppGallery**				

COPIERWORKS.COM

Xerox® AltaLink® C8230/C8235/C8245/C8255/C8270 Color Multifunction Printer

Security	AltaLink® C8230	AltaLink® C8235	AltaLink® C8245	AltaLink® C8255	AltaLink® C8270
Features	• Audit Log • Cisco® Identity Services Engine (ISE) compatible • Configuration Watchdog (Monitors and remediates 75 security settings in the following areas): - 802.1x - Admin Password Reset - Audit Log - Automatic Software Upgrade - Email Alerts - FIPS 140-3 (interim certification) - Hold All Jobs - Installation Policies - Job Data Removal - Trellix Embedded Control - PII - Login Name - PostScript Passwords - Remote Services Enablement - Remote Start (Mopria® or AirPrint™) - Remote Start (TWAIN) - Reprint Saved Jobs - Scan to Mailbox (Internal storage) - Secure Passcode Length - Secure Print Device Policies - SIEM - SNMP - System Timeout - USB (Print from USB) - USB (Scan to USB) - USB Port Management - User Data Encryption • Disable FTP • Erase Customer Data securely removes all data from SSD • Expanded Authentication - Encrypted and authentication to SMTP server for Scan to Email - Encrypted/Password Protected PDF (when using Email and Network Scan Templates only) - FIPS 140-3 (interim certification), 256 bit Hard Disk Encryption, TLS 1.1/1.2/1.3, IPPS, HTTPS, sFTP, SNMPv3 - Local Authentication (internal database) - NFC tap authentication with Xerox® Easy Assist App - Network authentication to access device and/or device services via Kerberos (UNIX/Windows Server 2008), SMB (Windows Server 2008, Windows server 2012), NDS, LDAP authentication - Smart Card authentication – 144k CAC/PIV Card Support (2048 bit certificate key)/.NET - Secure Data - USB PIV Security tokens such as Yubikey (requires the installation of the USB Token Hub kit) • Expanded Authorization - Authorization per user per service - SA access based on network credentials - Secure Network Access - User Permissions required to access Print and Print Features (e.g., color access, or time restrictions) reflects in the print driver • Full System Common Criteria Certification under collaborative Protection Profile for Hardcopy Devices (HCD cPP v1.0E) pending will be made available in a future firmware release • Hide Print Job Names • Imaging Security • IP Filter, IPsec, IPv6, TLS V1.1, V1.2, V1.3, SNMP V1/V2/V3, HTTPs, 802.1X, sFTP • Job Data Removal on SSD • Secure Print (up to 10 digit PIN or Network Authentication) • Security Dashboard • SIEM support using Common Event Format (CEF), such as Trellix ESM, LogRhytm, Splunk, and any cloud-based SIEM that uses an on-premises collector-forwarder that utilizes the syslog format, for example Microsoft® Sentinel • Security Templates • Trellix Embedded Control (allowlisting), Trellix Integrity Control (optional) • Trusted Platform Module 2.0 • USB port disablement • WPA2™ and WPA3™ are supported by the Dual Band Wi-Fi® and Bluetooth® Kit				
Xerox® Integrated RFID Card Reader (Optional Kit)	Integrated support for most industry security cards providing additional security; with embedded multifunction printer card readers in the multifunction printer panel				

copierworks.com

Xerox® AltaLink® C8230/C8235/C8245/C8255/C8270 Color Multifunction Printer

Fax	AltaLink® C8230	AltaLink® C8235	AltaLink® C8245	AltaLink® C8255	AltaLink® C8270
Network Server Fax Features					
Compatibility	ITU (CCITT) group 3; Various Xerox® Business Innovation Partner Solutions				
Maximum Scan Area	11 x 17 in./A3				
Fax Send Features	One- or Two-sided Scanning (up to 11 x 17 in./A3) Add to Send List (200 numbers maximum) Build Job, Favorites, Delay Send (specific time) Original Type (photo, text or photo and text)				
Fax Print Features	One- or Two-sided Printing, Staple, Secure Print				
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi				
Walk-up Fax Features (Optional; Customer-installable – 1 and 2 lines)					
Compatibility	ITU (CCITT) Group 3				
Speed/Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time				
Compression/Speed	MH/G3, MR/G3, MMR/SG3, JBIG/SG3				
Resolution	**Walkup Send:** Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi **Receive:** Accepts all sizes				
Fax Send Features	Auto Fax Transmission Reduction Automatic Cover Sheets Automatic Memory Resend Batch Send (up to memory capacity) Delay Start, Build Job, Favorites Device Address Book (up to 5,000 contacts) LAN Fax (fax from print driver) Page-by-page Job Status at the Machine PSTN Fax Support for Fax over Voice over IP Touchless Workflow Accelerators				
Fax Receive Features	Auto Answer Delay One- or Two-sided Printing Output Tray Selection Receive Print Mode – Manual (size, margin, stock, header)/Auto Receive Timestamp Secure Receive Stapled or Unstapled Support for Fax over Voice over IP Up to 200 Password Protected Mailboxes				
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only				
Fax Reports	Activity, Transmission Confirmation, Pending Fax, Options Report, Mailbox Report, Broadcast Report				
Directory Access	Utilizes the Unified Address Book Group fax available				
Auto Redial	Up to 14 attempts (per country requirements) 1 to 25 minute intervals				
Auto Resend	Up to 5 attempts				

Copierworks.com

Xerox® AltaLink® C8230/C8235/C8245/C8255/C8270 Color Multifunction Printer

Device Management	
Administrative Protocols	DHCP, BOOTP, SNMP, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System-Power MIB, Fleet Orchestrator, Configuration Watchdog, Security Dashboard, Xerox® Easy Assist App
Xerox® CentreWare® Web Software	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running on Windows, UNIX, or any other operating system: • Works with any SNMP-managed printer from any manufacturer • Remote configuration of SNMP v3 • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management • Requires Windows 7 and Internet Explorer 6.0 and higher • Auto-detect Xerox® CentreWare® Web server and download configurations files for touchless remote install
Xerox® Device Manager	**Optional:** Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to configure, manage, monitor, and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Support for Xerox Printer Security Audit Service and Advanced Security Services • Remote configuration of SNMP v3 • Extensive reporting and discovery of new devices • Usage collection, chargeback, and billing capabilities • Auto-detect Xerox® Device Manager server and download configurations files for touchless remote install
Xerox® Workplace Cloud Fleet Management	**Optional:** Xerox® Workplace Cloud Fleet Manager collects and manages the data that drives fact-based decisions for your device management environment, from SMB to Enterprise. It is a cloud-based tool with minimal to no on-site hosting required, to configure, manage, monitor, and report on networked devices – regardless of vendor – across your organization. Xerox® Workplace Cloud Fleet Management provides: • Device monitoring and troubleshooting • Support for Xerox Printer Security Audit Service and Advanced Security Services • Remote configuration of SNMP v3 • Extensive reporting and discovery of new devices • Usage collection, chargeback, and billing capabilities • Part of the integrated Xerox Workplace platform for Fleet Management and Print Management
Accessibility	• Embedded Web Server conforms to Web Content Guidelines (WCAG) • Private listening support via USB headphones/USB audio adapter • Touchscreen tilt and user interface inversion • Touchscreen zoom and pan • Touchscreen navigation with keyboard • Speech output
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files, and 1-Touch App files. Auto-assembly feature allows a new AltaLink to automatically set itself on the network and configure
Novell NDPS/NEPS	Server gateway application: centralized management tool
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® Device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download **office.xerox.com/Software-Solutions**
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at **office.xerox.com/Software-Solutions**
Xerox® Embedded Web Server – Integrated Device Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts • Remote Control Panel
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard, Security Templates
Browsers	Microsoft Edge version 88+ Microsoft Chromium Edge version 79+ Mozilla Firefox 91.9.0, 100.0 Safari 13.1.2, 14.1.2, 15.4 Opera 2020, 2021 Google Chrome version 80.0.x+
Support	Install print/scan drivers and online support available via **support.xerox.com**
Languages Supported	US English, Danish, German, Spanish, French, Croatian, Italian, Dutch, Norwegian, Brazilian Portuguese, Finnish, Swedish, Russian, Ukrainian, Arabic
Remote Services	
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time
Xerox® Automatic Supplies Replenishment (ASR)	Automatically orders supplies for output devices from Xerox based on actual usage, eliminating the need to manually manage supplies inventory

COPIERWORKS.com

Xerox® AltaLink® C8230/C8235/C8245/C8255/C8270 Color Multifunction Printer

Accounting	
Xerox® Standard Accounting Feature (Standard)	
Tracking	Copy, Print, Fax, Scan, and Email usage
Accounting	Up to 2,497 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group Accounts (Department)
Features	• Administrator can manage the feature via the Web User Interface or device control panel in tools • Administrator has the ability to import or export User Accounts, Group Accounts, General Accounts, and User Limits via an industry standard CSV file
Accounting Options – Network Accounting (Allows central server to manage all accounting)	
	• Enhanced network accounting with up-to-the-minute data on how the system is being used • Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan, and server fax • Numerous solutions are available through Xerox Alliance Partners. For details, visit **www.xerox.com** • Security enhancements with the addition of HTTPS protocol support • Device requests account authentication from third-party server enabling larger databases of users and accounts • Accept Authentication Login at control panel and pass to third-party Networking Account • Interface with third-party accounting terminal for accounting user interface
Xerox® EX-c AltaLink® Print Server Powered by Fiery® (Optional)	
Processor	AMD® GX-424CC processor, 2.4 GHz, Quad-Core, 2M cache
Memory (ESS)	2 GB
System Disk	500 GB HDD
File Format Support	PostScript, PDF, TIFF, EPS, Fiery FreeForm Create. Microsoft® Office document formats docx, xlsx, pptx, pub via the Fiery Driver or optional Fiery Hot Folders
Features	Access Controls Automatic two-sided printing Booklet Maker – booklet wizard to create booklets Calibration Digitally Signed Software Updates Expert Color Settings: Profile, Rendering, and Simulation Encryption of critical information Fiery API Fiery Command WorkStation for Mac and Windows clients (customer provided) Fiery drivers for Mac and Windows Fiery FreeForm Create to create personalized files for free Image Enhance IP Filtering Integrates with common cost accounting software, Xerox® Standard Accounting, Xerox® App Gallery Apps, and more Job Preview Job Presets N-up PANTONE® Color Enabled Print from USB flash drive PostScript Security Port Blocking Secure Erase Secure Printing Spool-RIP-Print simultaneously Standard support for long sheet banners User Authentication Watermarks
Connectivity	10Base-T/100Base-TX/1000Base-T Ethernet
Optional	Fiery Options Bundle (Fiery Spot-On, Auto Trapping, Hot Folders, Virtual Printers), Fiery Hot Folders/Virtual Printers, Fiery Spot-On, Fiery Color Profiler Suite w/Fiery ES-3000 Spectrophotometer, Fiery Hub Kit to connect both printer and Fiery Server to network

COPIERWORKS.COM

Supplies	Description	Yield
Toner Cartridge[6]	Black Cyan Magenta Yellow	59,000 pages 28,000 pages 28,000 pages 28,000 pages
Transfer Belt Cleaner	1 Assembly	160,000 pages
Second Bias Transfer Roll	1 Assembly	200,000 pages
Staple Cartridges	For BR Finisher, Integrated Office Finisher, Office Finisher, and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge
	For BR Booklet Maker (1 cartridge per carton)	5,000 each cartridge
	For Office Finisher Booklet Maker (8 cartridges per carton)	2,000 each cartridge
Staple Refills	For Integrated Office Finisher, Office Finisher, BR Finisher, and Convenience Stapler (3 refills per carton)	5,000 each refill
Fan Filter	1 Assembly (AltaLink® C8270)	500,000 pages
Xerox® Smart Kit® Technology		
Drum Cartridge[7]	1 Cartridge per Color	180,000 pages
Waste Toner Container w/o Suction Filter[8]	1 Cartridge (AltaLink® C8230/C8235/C8245/C8255)	69,000 pages
Waste Toner Container with Suction Filter[8]	1 Cartridge (AltaLink® C8270)	69,000 pages

[1] Declared in accordance with ISO/IEC 24734.
[2] Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
[3] Not available in all geographies.
[4] Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.
[5] Sold separately in some geographies.
[6] Average standard pages. Declared in accordance with ISO/IEC 19798. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes, and image quality set-points.
[7] Average drum yield is based on a run length of 5 pages of 8.5 x 11 in./A4 LEF pages, with split of 35% color/65% black-and-white pages.
[8] Waste Toner Container yield will vary depending on type of image, area coverage %, and job run length.

Copier Works.com

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program.
For more information, visit **www.xerox.com/About-Xerox/Recycling**.

For more information, visit us at **www.xerox.com/Office**.

© 2025 Xerox Corporation. All rights reserved. Xerox®, AltaLink®, CentreWare®, ConnectKey®, Smart Kit®, DocuShare®, and Global Print Driver® are trademarks of Xerox Corporation in the United States and/or other countries. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Mopria is a trademark of the Mopria Alliance®. AirPrint™ and iBeacon™ are trademarks of Apple Inc., registered in the U.S. and other countries. The Bluetooth® word mark is a registered trademark owned by the Bluetooth SIG, Inc. and any use of such marks by Xerox is under license. Wi-Fi® and Wi-Fi Direct® are registered trademarks of Wi-Fi Alliance®. WPA2™ and WPA3™ are trademarks of Wi-Fi Alliance®. The information in this brochure is subject to change without notice. 06/25 TSK-7022 BR41456 AC8SS-04UC EMC24043